

HTX Transmitter




The HTX and HLTX transmitters use a high precision temperature and humidity sensor which is accurate to +/- 1% rh (+/- 0.2°C) and can be attached either directly to the transmitter or via an extension cable for monitoring hard to reach areas or for in display cases.

Available in either a black or white enclosure the HTX transmitter ensures discreet and reliable monitoring in display cases and public spaces as well as stores and archives.

Transmitter address and transmission intervals can be programmed by the user without the need for any further equipment and the units can be wall mounted or left freestanding for added flexibility.

If required the HTX can be adapted to include a Lux and UV sensor (HLT) and the display then shows a continuous flow of all four readings (temperature / humidity / lux / UV). This enables more cost efficient monitoring of all conditions in one compact unit.

The HTX unit has a clear display which shows the current readings taken directly from the last transmission as well as having a low battery warning and a transmission indicator providing essential information at a glance.



TECHNICAL DATA

DIMENSIONS	85mm x 70mm x 40mm (sensor 100mm, aerial 160mm)
WEIGHT	257g inc batteries
POWER SUPPLY	4 x AA batteries
BATTERY /LIFE	At least 2 years under normal conditions
FREQUENCY	434.075 MHz
RANGE	5km over open ground
TEMPERATURE ACCURACY	+/- 0.2°C
HUMIDITY ACCURACY	+/- 1% rh