

Testo Data loggers

Testo offer a wide range of temperature and temperature/humidity data loggers to cater for a wide range of applications. Below are loggers that record both temperature and humidity.

These loggers are available with an extensive range of accessories and download options including a portable data stick and portable printer.



Technical data:

| | 175-H1 | 175-H2 | 177-H1 |
|-----------------|---------------------------|---------------------------|--|
| Parameter | Humidity/temperature | | Humidity/temp/dew point |
| Channels | 2: %rh, °C | 2: %rh, °C | 4: %rh, °C, °Ctd & external °C |
| Measuring range | 0...100%rh -10...+50°C | 0...100%rh -20...+70°C | 0...100%rh, -20...+70°C internal -40°C...+120°C external |
| Resolution | 0.1%rh/0.1°C | | |
| Accuracy | ±3% ±0.5°C | | ±2% ±0.4°C |
| Memory | 3,700 readings | 16,000 readings | 48,000 readings |
| Dimensions | 82mm x 52mm x 30mm | | 103mm x 64mm x 33mm |
| Operating temp | -10°C to +50°C | -20°C to +70°C | -20°C to +70°C |
| Battery type | Lithium 1/2AA 3.6V | | |
| Weight | 80g | 85g | 130g |



t: 0845 838 6963 e: information@meaco.co.uk f: 0845 838 6965